

TECHNICAL DATA**RR 125 ENDURO****CHASSIS**

| | |
|-------------------------|---|
| Frame | Molybdenum steel with double cradle split above the exhaust port |
| Wheelbase | 1477 mm |
| Max length | 2167 mm |
| Max width | 830 mm |
| Max height | 1270 mm |
| Seat height | 930 mm |
| Ground clearance | 325 mm |
| Footrest height | 410 mm |
| Dry weight | 94,0kg (front 45,0 kg; rear 49,0 kg) |
| Fuel tank capacity | 9,5 l. |
| Reserve | 2,3 l. |
| Cooling system capacity | 1,3 l. |
| Front suspension | Hydraulic USD fork with \varnothing 48 mm shaft |
| Rear suspension | Monoshock with progressive compound lever |
| Shock absorber stroke | 132 mm |
| Front wheel travel | 295 mm |
| Rear wheel travel | 290 mm |
| Front brake | Wave disc \varnothing 260 mm and double-piston floating caliper |
| Rear brake | Wave disc \varnothing 240 mm and single-piston floating caliper |
| Front rim | 21 x 1,6 - 36 fori |
| Rear rim | 18 x 1,85 - 36 fori |
| Front tyre | 90/90 - 21 |
| Rear tyre | 120/90 - 18 |

ENGINE

| | |
|----------------------|--|
| Type | Single cylinder, 2-stroke, liquid-cooled |
| Bore | 54 mm |
| Stroke | 54,5 mm |
| Displacement | 124,8 cc |
| Compression ratio | 15,2:1 |
| Exhaust Valve | BPV system |
| Starter | kick starter |
| Ignition | AC Kokusan - digital CDI |
| Spark plug | NGK BR9ECMVX |
| Induction system | induction reed |
| Lubrication | mixing |
| Carburettor | Keihin PWK 36 |
| Clutch | wet multi-disc with reverse opening |
| Primary drive | Z.23/73 |
| Transmission | 6 gears |
| Final transmission | chain |
| Engine oil | SAE 10W/40 |
| Consumption l/100 km | 3,3 |
| Pollution Co2 [g/km] | 76,2 |